Notified Body Nr. 0036



Certificate of conformity of the factory production control

0036 CPR 9184 001 Revision 08

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

System chimney, flue liner of rigid and flexible pipes and fittings of PP models

without outer liner, rigid	EN 14471	T120 H1 W2 O20 LX E U
with metal outer liner, rigid	EN 14471	T120 H1 W2 O00 LE E U0
with plastic outer liner, rigid	EN 14471	T120 H1 W2 O00 LI E U1
with metal outer liner, rigid	EN 14471	T120 H1 W2 O00 LE E U0
with mineral shaft, flexible	EN 14471	T120 H1 W2 O00 LE E U0

for details of classification see page 2

produced by

Skoberne GmbH Ostendstraße 1 64319 Pfungstadt

in the manufacturing plant

Werk 2

Werk 3

Werk 5

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 14471:2013+A1:2015

under system 2+ are applied and that the factory production control fulfils all the prescribed requirements set out above.

The determination of the product type on the basis of type testing is documented in the following report: TÜV SÜD Industrie Service GmbH no. A 1614-00/06, A 1614-02/09, A 1614-03/09, A 1614-04/09, A 1614-05/10, A 1614-06/10, A 1614-07/10, A 1614-09/12, A 1614-14/16, A 1614-17/16, A 1614-19/20 and A 1614-20/22.

This certificate was first issued on 2007-02-27 and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performance of the declared characteristics, do not change, and the product, and the manufacturing conditions in the plant are not modified significantly.

Munich, 2022-03-10

Johannes Steiglechner Leiter Zertifizierungsstelle Bauprodukte

Page 2 of certificate no.

0036 CPR 9184 001 Rev. 08



System chimney with flue liner of rigid and flexible pipes and fittings of PP

EN 14471

without outer liner, rigid 0.1 DN 60 - DN 110, black 0.2 DN 60 - DN 250, white

0.3 DN 60 – DN 250, grey

T120 H1 W2 O20 LE E U T120 H1 W2 O20 LI E U T120 H1 W2 O00 LI E U

with metal outer liner, rigid 0.4 DN 60 - 80

T120 H1 W2 O00 LE E U0

0.4 014 00 00

with plastic outer liner, rigid 0.5 DN 60 - DN 80

T120 H1 W2 O00 LI E U1

with metal outer liner, rigid white, grey, black 0.6 DN 110 – DN 160

T120 H1 W2 O00 LE E U0

with mineral shaft, flexible, white 0.7 DN 60 – DN 110

T120 H1 W2 O00 LE E U0